



### PRODUCT FEATURES

- 450 Lumen 7W white 6500K COB LED
- Additional 450 lumen 3W 6500K CREE LED spot beam with magnifying collimator lens for long distance beam
- Ultra tough nylon & TPR construction
- 360° Rotating stand/handle with super strong magnets
- Memory switch - remembers last mode used
- IP65 Dust & water resistant
- IK07 Shock proof - 2M drop resistant
- Powerful 3.7v 1500mAh Li-polymer battery
- Battery level & charging indicator LED under the switch
- Fast 3A USB-C charging - 2.5 hour charge time
- Supports fast 'USB PD' (power-delivery) charging
- 1m high quality USB-C cable included

**BATTERY** - 3.7v 1500mAh Li-polymer rechargeable battery

**WEIGHT** - 145g

**DIMENSIONS** - 69.5 x 34.1 x 85.7mm

### ADVICE & IMPORTANT INFORMATION!

- Do not look directly at LEDs.
- Do not operate in direct sunlight or extreme temperature conditions (below -10°C or above 40°C).
- LEDs can become warm/hot when switched on; DO NOT touch and NEVER place face down on any surface - risk of fire! Even once the device has been switched off, DO NOT place face down as the LED and Lens can stay hot/warm for a while.
- Do not use the device if there is any visible damage.
- Do not use the device in the immediate vicinity of flammable materials or gases.
- Take care when charging, check the charging output on the charging source you are using and DO NOT exceed the stated Max charging input or damage may occur to the battery and may void the warranty.
- The rechargeable battery will reach full performance after a few complete charging and discharging cycles.
- To keep the rechargeable battery in optimum condition, it should be recharged every 3-6 months, especially if it is not being used for a long period of time.
- Always fully charge rechargeable batteries before storage and if the rechargeable battery can be removed, this is advised to avoid battery depletion and avoids the risk of a battery leaking.
- Always protect lithium batteries from heat, intense sunlight, fire, water and moisture - danger of explosion!
- If a battery is damaged, fluids can leak out. AVOID contact as this can lead to skin irritation and/or burns. If skin contact occurs, rinse thoroughly with water. If irritation persists, seek medical advice. Seek immediate medical

### ANSI FL1 Standard



	450 Lumen	34 M	2.5 H
SPOT BEAM	450 Lumen	34 M	2.5 H
FLOODLIGHT - LOW	125 Lumen	11 M	6 H
FLOODLIGHT - HIGH	450 Lumen	29 M	2.5 H

### OPERATING INSTRUCTIONS

SWITCH SEQUENCE:- Spot Beam > Floodlight Low > Floodlight High > Off

Memory Switch - If left On in any mode for over 5 seconds, the next press will turn off. Next press On will return to the last mode used.

### RECHARGING

1. Only use a 5V USB-C charging cable.
2. Lift the charging port cover on the back of the light.
3. Plug the USB-C end of the cable into the charge port.
4. Plug the USB-A end of the cable into a USB charging source (do not exceed 5V-3A charging input or damage may occur).
5. Green Flash indicates charging, Solid Green indicates fully charged.
6. Charge Time: 2.5 hours
7. Make sure the charge port cover is secured back in place.

(THIS PRODUCT CAN NOT BE USED WHILE RECHARGING)

*\*Warranty void if not used with the specified cable & max charge input\**

### CHARGING INDICATOR

- Green Flashing = charging
- Solid Green = fully charged

### BATTERY LEVEL INDICATOR

NOTE: Battery indicator lights up for 10 seconds when the worklight is first turned on.

- Green = 65% - 100%
- Orange = 30% - 65%
- Red = 5% - 30%
- Red Flashing = less than 5%

- assistance if lithium battery fluid comes into contact with the eyes.
- Children under 12 years of age should only use the product under adult supervision.
- Do not disassemble or attempt to modify the product; this will void the warranty and can be dangerous. Improper use or modification is not covered under the warranty.
- Take care not to let lenses come into contact with hard/sharp objects, damage/scratches to lenses will affect light output.
- Do not use the product in the immediate vicinity of flammable materials or gases.
- Before cleaning the product, disconnect the charge cable. Clean with a dry or slightly moist, clean, lint-free cloth and a mild detergent if required. Do not use cleaners that contain abrasives or solvents.
- This product is water resistant to IPX5 - DO NOT SUBMERGE. If the product has been subjected to excessive moisture/water the warranty may be void.
- This product has a 1 year standard warranty (or extended to 2 years once registered online at [WWW.UNILITE.CO.UK/WARRANTY](http://WWW.UNILITE.CO.UK/WARRANTY)) against manufacturing faults and defects. It does not cover normal wear and tear, modifications, accidental damage or poor maintenance. Unilite standard warranty does not cover disposable batteries that have leaked or the use of incorrect chargers and cables that can damage rechargeable batteries.
- Do not dispose of this device in normal household waste. It must be disposed of via an authorised electrical appliance disposal centre or at your local waste disposal unit.
- Please re-use or recycle packaging responsibly.
- Keep these instructions for future reference or for subsequent possessors.